

Vシリーズ防舷材 SV-R型 200H

性能

| 規格   | 長さ<br>(m) | ゴム質 | 設計変位量 45.0% |                   | 質量<br>(kg) |
|------|-----------|-----|-------------|-------------------|------------|
|      |           |     | 反力<br>(kN)  | 吸収エネルギー<br>(kN・m) |            |
| 200H | 1.0       | VR0 | 184         | 12.3              | 50         |
|      |           | VR1 | 168         | 11.2              |            |
|      |           | VR2 | 147         | 9.81              |            |
|      |           | VR3 | 110         | 7.38              |            |
|      |           | VR4 | 73.6        | 4.91              |            |
|      | 1.5       | VR0 | 276         | 18.4              | 75         |
|      |           | VR1 | 252         | 16.8              |            |
|      |           | VR2 | 221         | 14.7              |            |
|      |           | VR3 | 166         | 11.1              |            |
|      |           | VR4 | 110         | 7.36              |            |
|      | 2.0       | VR0 | 368         | 24.5              | 100        |
|      |           | VR1 | 336         | 22.4              |            |
|      |           | VR2 | 294         | 19.6              |            |
|      |           | VR3 | 221         | 14.8              |            |
|      |           | VR4 | 147         | 9.81              |            |
|      | 2.5       | VR0 | 459         | 30.7              | 125        |
|      |           | VR1 | 419         | 28.0              |            |
|      |           | VR2 | 368         | 24.5              |            |
|      |           | VR3 | 276         | 18.4              |            |
|      |           | VR4 | 184         | 12.3              |            |
|      | 3.0       | VR0 | 551         | 36.8              | 150        |
|      |           | VR1 | 503         | 33.6              |            |
|      |           | VR2 | 441         | 29.4              |            |
|      |           | VR3 | 331         | 22.1              |            |
|      |           | VR4 | 221         | 14.7              |            |
|      | 3.5       | VR0 | 643         | 42.9              | 175        |
|      |           | VR1 | 587         | 39.1              |            |
|      |           | VR2 | 515         | 34.3              |            |
|      |           | VR3 | 387         | 25.8              |            |
|      |           | VR4 | 258         | 17.2              |            |